

# URZĄDZENIA ZDAWCZE

Typ urządzenia	Zakres średnic kabli i przewodów	Max. prędkość liniowa	Średnica tarczy szpul i bębnow	Max. ciężar szpul	GABARYTY			Ciężar urz.
					L	B	H	
	mm	m/min	mm	kG	mm	mm	mm	kG
<b>URZĄDZENIA ZDAWCZE O NIERUCHOMEJ SZPULI</b>								
<b>AG630D</b>	0,4–2,5	1200	2 x (315 - 630)	2 x 500	2800	1300	3100	1000
<b>AG630S</b>	0,4–2,5	1200	315 - 630	500	1400	1300	3160	700
<b>URZĄDZENIA ZDAWCZE NAPĘDZANE</b>								
<b>AH630</b>	0,15–1,0	400	630	800	800	1000	1600	200
<b>A630N</b>	0,6–1,9	300	630	200	1200	800	900	250
<b>A800N</b>	0,5–3,0	300	400 - 800	800	1355	810	1525	550
<b>A1000N</b>	1,0–5,0	300	500 - 1000	1500	1800	810	1500	900
<b>A1250N</b>	2,0–30,0	300	630 - 1250	3000	1850	1000	1550	1000
<b>A1600N</b>	6,0–45,0	200	800 - 1600	4000	2100	1250	1650	1250
<b>URZĄDZENIA ZDAWCZE NIENAPĘDZANE</b>								
<b>A630</b>	1,8–5,0	100	630	800	1200	800	900	120
<b>A800</b>	0,5–3,0	150	200–800	800	1355	810	1525	400
<b>A1000</b>	1,0–5,0	200	500–1000	1000	1800	810	1500	500
<b>A1250</b>	2,0–15,0 (30)	200	630 - 1250	1200	2300	1300	2050	600
<b>A1600</b>	4,0–20,0 (40)	150	800 - 1600	1500	2500	1650	2200	700
<b>URZĄDZENIA ZDAWCZE NAPĘDZANE TRAWERSUJĄCE</b>								
<b>A2000T</b>	4,0–60,0	100	1000–2000	4000	2000	3500	3250	2200
<b>A2500T</b>	20,0–75,0	50	1250 - 2500	5000	4000	3500	2500	2900
<b>A2800T</b>	20,0–80,0	50	1600 - 2800	10000	4500	3800	2800	3200



<http://www.manex.com.pl>