

# WYTŁACZARKI

Typ wyciarki	Wymiar ślimaka fi/L [mm]	Max. prędkość obrotowa [1/min]	Max. wydajność PVC/PE [kg/h]	Moc silnika/grzania [kW]	GABARYTY			Ciężar urządź [kg]
					L	B	H	
					[mm]	[mm]	[mm]	
<b>WYTŁACZARKI JEDNOŚLIKOWE DO TWORZYW SZTUCZNYCH</b>								
<b>E16H</b>	16/25D	140	4/2,5	1,5/2,0	1150	500	1500	220
<b>E25H</b>	25/25D	200	15/10	3/3,6	1350	500	1500	250
<b>E25V</b>	25/25D	200	15/10	3/3,6	600	500	2700	280
<b>E32</b>	32/25D	180	50/35	9,2/5,5	1400	870	1700	350
<b>E45</b>	45/25D	180	100/70	30,0/8,0	1900	960	1870	500
<b>E60</b>	60/25D	160	200/140	59/14,5	2450	960	2000	1100
<b>E90</b>	90/25D	130	400/280	90/26,5	3500	1200	2100	2800
<b>E120</b>	120/25D	105	600/420	130/39,5	4400	1500	2270	4500
<b>E150</b>	150/25D	82	950/670	250/82	5700	1960	2470	8500
<b>WYTŁACZARKI DWUŚLIKOWE</b>								
<b>E50B</b>	2x48/6D	40	20/15	4/2,8	1740	680	1680	400
<b>WYTŁACZARKI JEDNOŚLIKOWE DO MIESZANEK GUMOWYCH</b>								
<b>E30G</b>	30/10D	70	25	2,5/2,2	1900	800	2380	350
<b>E45G</b>	45/15D	120	150	22/9,5	1800	1300	1500	1750
<b>E90G</b>	90/15D	82,5	500	54/13,4	2490	1470	1580	2250
<b>E120G</b>	120/15D	70	800	75/16,5	3550	1600	1660	3800
<b>E150G</b>	150/15D	56	1400	140/36	4215	1870	1800	10300



<http://www.manex.com.pl>